



CO2 Liquid / Vapour Charging Rig



A complete CO2 trans critical charging rig

- Including: 300 bar maximum inlet pressure
- Liquid CO2 Charging connector
- ¼" 2m High Pressure hose
- 1/4" SAE female flare outlet, for direct connection to system
- Direct connection to CO2 cylinder

Description	Part No.
CO2 liquid / vapour charging rig	JAV-2000-144
Kit includes:	
1 x PVR Manifold, 2 x Stainless Steel 1 x 2m CO2 hose, 2 x anti-whip cables, 1 x shut-off ball valve with CO2 bottle connector	

CO2 sub and trans critical manifolds



- 2 or 4 valve manifolds with 80mm diameter oil filled gauges
- Sub: LP -1 to +30 Bar, HP -1 to +50 Bar
Trans: LP -1 to +80 Bar, HP -1 to +160 Bar
- Set of 3 charging lines 1m long.
- Sturdy plastic carry case.

Description	Type	Part No.
CO2 2 valve	Sub critical	FR1304-E20
CO2 4 valve	Sub critical	FR1308-4R-E20
CO2 2 valve	Sub critical	4687894
CO2 2 valve	Trans critical	FR4312-E25



FR1304-E20



FR1308-4R-E20



FR4312-E25



4687894