



Safety Swivel
One-touch design

Safe Seal

CHARGING HOSES



Patented Safe Seal technology: 'One-Touch' design allows you to screw the fitting on to the system before starting refrigerant flow, avoiding refrigerant loss and risk of 'refrigerant burn'. Then simply turn the knob to start/stop flow.

- 72" hose (183cm), Suitable for standard refrigerants.
- The safety swivel sleeve allows free rotational movement of the hose without the fitting coming loose being put under unnecessary strain and preventing unwanted leaks

Description	Part No.
Charging Hoses, Safe Seal, 1/4", Working Pressure: 600/3000 PSI (41 bar) Bursting pressure of 3000 psi (207 bar)	JAV-1071

R410A/R32 Charging Hoses, Safe Seal, 1/4" x 5/16", Working Pressure: 800/4000 PSI (55 bar). Bursting pressure of 4000 psi (276 bar)	JAV-1072
---	----------

Safe Seal Hose Gaskets	Part No.
Safe Seal Gasket Manifold End 1/4" (10 pack)	JAV-1374
Safe Seal Gasket Serve End 5/16 x 1/4" (10 pack)	JAV-1276
Safe Seal O-ring for 5/16"	JAV-1355
Safe Seal O-ring for 1/4"	JAV-1354